

---

# Test Builds

Nov 19, 2019



---

## Contents

---

<b>1</b>	<b>conf.py</b>	<b>3</b>
<b>2</b>	<b>Test Builds</b>	<b>9</b>
2.1	Scenarios . . . . .	9
2.2	Tags . . . . .	10
2.3	Addind a new scenario to the repository . . . . .	10



All contents of this documentation.



# CHAPTER 1

conf.py

```
1  # -*- coding: utf-8 -*-
2
3  # Default settings
4  project = 'Test Builds'
5  extensions = [
6      'sphinx_autorun',
7  ]
8
9  latex_engine = 'xelatex' # allow us to build Unicode chars
10
11
12  # Include all your settings here
13  html_theme = 'sphinx_rtd_theme'
14
15
16
17
18  #####
19  #          auto-created readthedocs.org specific configuration          #
20  #####
21
22
23  #
24  # The following code was added during an automated build on readthedocs.org
25  # It is auto created and injected for every build. The result is based on the
26  # conf.py.tpl file found in the readthedocs.org codebase:
27  # https://github.com/rtfd/readthedocs.org/blob/master/readthedocs/doc_builder/templates/
28  # ↪ doc_builder/conf.py.tpl
29  #
30
```

(continues on next page)

(continued from previous page)

```

31 import importlib
32 import sys
33 import os.path
34 from six import string_types
35
36 from sphinx import version_info
37
38 # Get suffix for proper linking to GitHub
39 # This is deprecated in Sphinx 1.3+,
40 # as each page can have its own suffix
41 if globals().get('source_suffix', False):
42     if isinstance(source_suffix, string_types):
43         SUFFIX = source_suffix
44     elif isinstance(source_suffix, (list, tuple)):
45         # Sphinx >= 1.3 supports list/tuple to define multiple suffixes
46         SUFFIX = source_suffix[0]
47     elif isinstance(source_suffix, dict):
48         # Sphinx >= 1.8 supports a mapping dictionary for multiple suffixes
49         SUFFIX = list(source_suffix.keys())[0] # make a ``list()`` for py2/py3
50     ↪ compatibility
51     else:
52         # default to .rst
53         SUFFIX = '.rst'
54 else:
55     SUFFIX = '.rst'
56
57 # Add RTD Static Path. Add to the end because it overwrites previous files.
58 if not 'html_static_path' in globals():
59     html_static_path = []
60 if os.path.exists('_static'):
61     html_static_path.append('_static')
62
63 # Add RTD Theme only if they aren't overriding it already
64 using_rtd_theme = (
65     ('html_theme' in globals() and
66     html_theme in ['default'] and
67     # Allow people to bail with a hack of having an html_style
68     'html_style' not in globals()
69     ) or 'html_theme' not in globals()
70 )
71 if using_rtd_theme:
72     theme = importlib.import_module('sphinx_rtd_theme')
73     html_theme = 'sphinx_rtd_theme'
74     html_style = None
75     html_theme_options = {}
76     if 'html_theme_path' in globals():
77         html_theme_path.append(theme.get_html_theme_path())
78     else:
79         html_theme_path = [theme.get_html_theme_path()]
80
81 if globals().get('websupport2_base_url', False):

```

(continues on next page)



(continued from previous page)

```

82 websupport2_base_url = 'https://readthedocs.org/websupport'
83 websupport2_static_url = 'https://assets.readthedocs.org/static/'
84
85
86 #Add project information to the template context.
87 context = {
88     'using_theme': using_rtd_theme,
89     'html_theme': html_theme,
90     'current_version': "2.5",
91     'version_slug': "2.5",
92     'MEDIA_URL': "https://media.readthedocs.org/",
93     'STATIC_URL': "https://assets.readthedocs.org/static/",
94     'PRODUCTION_DOMAIN': "readthedocs.org",
95     'versions': [
96         ("latest", "/en/latest/"),
97         ("stable", "/en/stable/"),
98         ("2.5", "/en/2.5/"),
99         ("2.4", "/en/2.4/"),
100        ("2.1.0", "/en/2.1.0/"),
101        ("2.1", "/en/2.1/"),
102    ],
103    'downloads': [
104    ],
105    'subprojects': [
106    ],
107    'slug': 'agj-test-automation-rules',
108    'name': u'agj-test-automation-rules',
109    'rtd_language': u'en',
110    'programming_language': u'words',
111    'canonical_url': 'https://agj-test-automation-rules.readthedocs.io/en/2.5/',
112    'analytics_code': 'None',
113    'single_version': False,
114    'conf_py_path': '/docs/',
115    'api_host': 'https://readthedocs.org',
116    'proxied_api_host': 'https://readthedocs.org',
117    'github_user': 'agjohnson',
118    'github_repo': 'test-builds',
119    'github_version': '2.5',
120    'display_github': True,
121    'bitbucket_user': 'None',
122    'bitbucket_repo': 'None',
123    'bitbucket_version': '2.5',
124    'display_bitbucket': False,
125    'gitlab_user': 'None',
126    'gitlab_repo': 'None',
127    'gitlab_version': '2.5',
128    'display_gitlab': False,
129    'READTHEDOCS': True,
130    'using_theme': (html_theme == "default"),
131    'new_theme': (html_theme == "sphinx_rtd_theme"),
132    'source_suffix': SUFFIX,
133    'ad_free': False,

```

(continues on next page)

(continued from previous page)

```

134     'user_analytics_code': '',
135     'global_analytics_code': 'UA-17997319-1',
136     'commit': 'd39922ff',
137 }
138
139
140
141
142 if 'html_context' in globals():
143
144     html_context.update(context)
145
146 else:
147     html_context = context
148
149 # Add custom RTD extension
150 if 'extensions' in globals():
151     # Insert at the beginning because it can interfere
152     # with other extensions.
153     # See https://github.com/rtfd/readthedocs.org/pull/4054
154     extensions.insert(0, "readthedocs_ext.readthedocs")
155 else:
156     extensions = ["readthedocs_ext.readthedocs"]
157
158 # Add External version warning banner to the external version documentation
159 if 'branch' == 'external':
160     extensions.insert(1, "readthedocs_ext.external_version_warning")
161
162 project_language = 'en'
163
164 # User's Sphinx configurations
165 language_user = globals().get('language', None)
166 latex_engine_user = globals().get('latex_engine', None)
167 latex_elements_user = globals().get('latex_elements', None)
168
169 # Remove this once xindy gets installed in Docker image and XINDYOPS
170 # env variable is supported
171 # https://github.com/rtfd/readthedocs-docker-images/pull/98
172 latex_use_xindy = False
173
174 chinese = any([
175     language_user in ('zh_CN', 'zh_TW'),
176     project_language in ('zh_CN', 'zh_TW'),
177 ])
178
179 japanese = any([
180     language_user == 'ja',
181     project_language == 'ja',
182 ])
183
184 if chinese:
185     latex_engine = latex_engine_user or 'xelatex'

```

(continues on next page)

(continued from previous page)

```
186
187     latex_elements_rtd = {
188         'preamble': '\\usepackage[UTF8]{ctex}\n',
189     }
190     latex_elements = latex_elements_user or latex_elements_rtd
191 elif japanese:
192     latex_engine = latex_engine_user or 'platex'
```



This repository is used internally to create different scenarios on build configs and trigger many builds on Read the Docs productions.

Each branch should explain on it's `docs/index.rst` what's about and how the QA process can be considered a success or a failure.

If we need to test a very specific use case, we create a new branch with the issue number and the repository, like: `issue-1234-org`, `issue-4321-ext` or similar.

## 2.1 Scenarios

Each of these scenarios is a branch that can be built independently from the others.

- `alabaster-theme`: use `alabaster` as theme
- `auto-wipe`: used for auto wipe the environment when a config is changed
- `branch/with/slashes`: used to check that git clones without problem
- `conda-env`: use a simple conda environment to build the docs
- `conda-env-py3.7`: use a simple conda environment to build the docs with Python 3.7
- `datetime`: shows different times (system time, build time, etc)
- `environment-variables`: shows all the environment variables used to build the docs
- `huge-build-output`: generate megabytes of output data for commands
- `none-formats`: use `formats: []` so only HTML is built
- `requirements-not-found`: use `requirements_file: .notfound.txt`
- `robots-txt`: use a custom `robots.txt` for this project
- `search-with-old-sphinx-and-theme`: search box on old Sphinx and RTD theme version
- `timeout`: generate a timeout by sleeping 1000 seconds

- `typlog-theme`: use `typlog` as theme
- `ũńĩč°də-branch`: the name of the branch is unicode
- `unicode-filename`: has a page (`rst`) that its filename is unicode
- `use-py2`: use `python: version: 2`
- `yaml-v2`: use a simple YAML for the V2 configuration

---

**Note:** There could be more scenarios probably, but this list is not always up to date. Please, check [all the branches](#) to be sure.

---

## 2.2 Tags

We also have some tags to have some tests around this.

- `tag-v1`: points to an specific commit
- `tag-v2`: points to the same commit than `tag-v1` (Delete tags with same commit)

## 2.3 Addind a new scenario to the repository

1. Create a new branch from `master` using an appropriate name
2. Explain what's the use case in its `docs/index.rst` file
  - How to check if the QA can be considered success or failure
  - Add links to the issue tracker where there are more information
3. Add or modify the necessary files
  - Make sure that these files contains the minimum configuration needed:
    - remove auto generated comments
    - configs not used
4. Push your changes
5. Modify the `README.rst` file from `master` to add this new branch in the list

---

Sphinx configuration file used to build this docs (*see full file*),

```
1  # -*- coding: utf-8 -*-
2
3  # Default settings
4  project = 'Test Builds'
5  extensions = [
6      'sphinx_autorun',
7  ]
8
9  latex_engine = 'xelatex' # allow us to build Unicode chars
10
```

(continues on next page)

(continued from previous page)

```
11
12 # Include all your settings here
13 html_theme = 'sphinx_rtd_theme'
14
15
16
17
```

---

```
>>> # Build at
>>> import datetime
>>> datetime.datetime.utcnow() # UTC
datetime.datetime(2019, 11, 19, 17, 43, 0, 76276)
```